# **APB SELECT DUAL AUGER**



## Rugged. Dependable.

Whether used for ice control, paver loading, berming or hauling, Swenson's APBs have a well-deserved reputation for their rugged dependability. The dual auger design with the enclosed trough ensures material won't leak onto the chassis and also increases the control of material output. Whether ordered in a standard configuration or with options and accessories, the APB with dual augers helps you get the job done right.

### swensonproducts.com

- DESIGNED FOR TRUCKS CLASS 6, 7, 8 (26,000+ LBS GVW)
- ► CAN BE CONFIGURED WITH A FLAT OR SLOPED FLOOR
- DIRECT DRIVE WITH TWO AUGERS FOR FASTER SPREADING
- ▶ FRONT-MOUNTED TELESCOPIC HOIST
- AVAILABLE IN DURABLE CARBON STEEL OR CORROSION-RESISTANT STAINLESS STEEL




## **APB SELECT DUAL AUGER**









Ladder

### **Features**



Adjustable spinner can be mounted on various height vehicles.



**Dual augers** provide double the material output.



Flush rear aprons provide safety, as well as an overall cleaner look to your spreader.



Optional top screens keep large chunks out of hopper and increase safety.

#### Highlights

- Direct drive with two augers doubles the output of material
- ▶ Hopper side slope available in flat, 22°, 38° or 45°
- Available in front discharge, rear discharge or both
- ▶ Double acting telescopic hoist with 20- or 40-ton capacity is front-mounted for a lower center of gravity, providing more stability
- ▶ 47° dump angle
- Double acting tailgate opens up for dumping or down for flat hauling
- ▶ Enclosed trough system prevents material leakage
- Adjustable spinner assembly with 20" poly disk fits a variety of vehicles, swings away for dumping
- ▶ Half-cab shield protects truck from damage during loading and unloading
- Carbon steel units are primed and ready to paint to match your fleet; also available in corrosion-resistant stainless steel

#### Equipment

| Construction             | Carbon steel or stainless steel  |
|--------------------------|--|
| Length                   | 9', 10', 12', 13', 14'   |
| Side height              | 40" or 46"   |
| Tailgate height          | 50" or 56"   |
| Cab-axle length          | 84", 96", 102", 108"   |
| Side height capacity     | 5.6 to 10.7 cu. yds.   |
| Tailgate height capacity | 7.5 to 13.7 cu. yds.   |
| Warranty                 | 1 year   |
| Options                  | Pre-wet system, ICC LED lights with harness, air tailgate, ladder, top screens |

#### **Materials**

| Clear Path Ice Melt |
|---------------------|
| Magnesium chlorid   |
| Treated rock salt   |
|                     |





