

T *rackless* V E H I C L E S



SERIES **MT7** – MUNICIPAL TRACTOR

FOR MAXIMUM PRODUCTIVITY, SAFETY AND COMFORT

... FROM **THE LEADER** IN THE MUNICIPAL TRACTOR FIELD

SPECIFICATIONS

ENGINE		STD	OPT
John Deere	Tier 4 Final		
Displacement	275 cubic inch, 4.5 litre	STD	
Horsepower	74 BHP @ 2,500 rpm		
Torque	224 lb-ft @ 1600 rpm		
Equipped with cold start aid, block heater Air breather warning light		STD	

FEATURES		STD	OPT
Certified R.O.P.S cab structure		STD	
Digital dash: tachometer, speedometer, hour meter, fuel level, engine coolant temp., hydraulic oil temp., engine oil pressure, voltmeter		STD	
7-speed heater / defroster / AC		STD	
Climate Controlled Air conditioning / auxiliary heat and pressurization with 8 amber strobe lights		STD	
2 outside and 1 inside rear view mirror		STD	
3 point retractable seat belt - Orange		STD	
AM / FM stereo, dual speakers, external aerial with amplifier		STD	
Cell phone holder, door pocket, storage tray		STD	
Front P.T.O		STD	
Tilt steering column with horn, self cancelling signal lever, hazard button		STD	
Left and right side slider windows		STD	
Intermittent front wiper and washer		STD	
Rear wiper and washer			OPT 27
High back, fabric covered air ride seat with lumbar support		STD	
20 gpm main hydraulic gear pump 14 gpm secondary hydraulic gear pump Low hydraulic oil warning		STD	
Reversing engine fan		STD	
F-N-R joystick		STD	
Battery disconnect switch		STD	
Remote battery terminal		STD	
Ride control		STD	
Cruise control		STD	
Fuel capacity of 92 Litres, 24 US Gallons		STD	

POWERTRAIN		STD	OPT
Sauer Danfoss hydrostatic / electronic transmission and motor		STD	
Control by electronic foot pedal programmed to control hydrostatic independently or both engine rpm and hydrostatic simultaneously		STD	
Trackless mechanical transmission with high / low range and neutral		STD	
10:1 deep reduction planetary transmission When coupled to mechanical transmission, 4 speed ranges instead of 2 Deep low is 0 – 10 feet / minute			OPT 9
Dana style Model 60 full float axles with new heavy duty alloy spindles Limited slip differentials 7,000 lbs capacity		STD	
Electric locking differential front axle only			OPT 10

SAFTY FEATURES		STD	OPT
Neutral safety start switch		STD	
Automatic hydraulic power shut offs if operator leaves seat		STD	
Automatic PTO shut down if operator leaves seat		STD	
Automatic engine shut down if operator leaves seat with shifter not in neutral position		STD	
Automatic hydraulic power shut offs if rotary wings are raised		STD	
Pinch point, danger, caution decals		STD	
Backup camera / Backup alarm		STD	
Articulation lock		STD	
Wire finger guard protection from engine fan blades Reflective striping on both sides and rear of tractor		STD	
External lift cylinder switch for attachment hookup		STD	

LIGHTS		STD	OPT
4 - Halogen headlights 1 - Halogen backup light 2 - Rubber mounted shockproof LED tail lights 1 - Interior dome light Front and rear signal lights and 4 way flashers - LED		STD	
Second rear backup light			OPT 15
Additional high mount rear tail lights			OPT 16
Headlight, signal / marker light guards			OPT 18