

PATENTED TURRET STYLE DESIGN



ALLOWS FOR MOWING
IN FRONT OF THE
TRACTOR TIRE

MAXIMUM PRODUCTIVITY AT A 30FT REACH

Packed with new features and all the power, precision, and performance as the original; the Maverick™ 2 stands alone when it comes to boom mowers. Reach high into trees, over the guardrails, down steep slopes, and around the waterways. Power through these tough mowing challenges with the ability to reach up to 30 feet. Maverick™ 2 is a smart design for those who want the most from their investment.



**the CuttingEdge
Safety program**

T.M.O.S.T.: Tractor Mower Operator
Safety Training



**ALAMO
INDUSTRIAL**

A Member of Alamo Group

BUILT SHARPER®

Alamo Industrial® | 1502 East Walnut Street, Seguin, TX 78155 | 800-882-5762 | www.alamo-industrial.com

© 2017 Alamo Group Inc. Registered trademarks identified are property of Alamo Group Inc.

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products. Warranty: Minimum one year parts and labor. Non-governmental users are subject to a modified policy. Only genuine Alamo Industrial parts may be used for warranty replacement.



FAN PLACEMENT

Improved positioning protects against branches and debris. Optional reverser allows for automatic cleaning.



TANK ASSEMBLY

Monoblock control valve assembly features 7-spool design with counterbalance valves. Improved oil capacity.



WELDED LINKAGE ARMS

Heavy duty welded linkage arms for head tilt operations allowing the head to be maneuvered up to 215°.



STEEL TANK COVER

Steel cover offers greater impact protection and improved access to components.

IT'S ALL IN THE DETAILS



The Maverick™ 2 Series is available in four reach options: 22', 24', 28', and 30'

Standard Specifications:

Telescopic Dipper Section:	24' Model= Up-21'10", Out-24', Down-14'8"
	30' Model= Up-27'10", Out-30', Down-19'3"
Fixed Dipper Section:	22' Model= Up-19'10", Out-22', Down-12'8"
	28' Model= Up-25'10", Out-28', Down-17'3"
Boom Weight:	10,000 lbs. (30' model)

All Alamo Industrial Kits include:

- Exclusive under-mount design - Large slewing bearing is utilized for enhanced boom maneuverability and 180° horizontal swing
- Electronic joystick control
- Hydraulic front axle stabilizer
- Polycarbonate door & window kit
- All additional counter weight necessary: Calcium chloride and/or steel

Tractor Requirements

- Minimum of 10,500 lbs. base tractor weight
- Minimum of 90 PTO HP (Tier IV-B (final) models)
- Minimum of 90" wheelbase and 18" ground clearance

Weights are approximate figures only. Variable factors on your order will conclude specific weights for each combination.

All tractor/mower combinations should be approved by Alamo Industrial engineering before order is placed.



SCAN HERE TO SEE THE MAVERICK™ 2 IN ACTION!



HOSE ACCESS + GUARD

Internal rubber hoses are replaced by external hard tubes, eliminating chafing and binding. Removable guarding allows easy access.



BOOM EXTENSION

Outer tube sliding design offers more robust and reliable operation.



PUCK DESIGN + PLACEMENT

Nylatron self-lubricating slide pucks. Strategic placement offers precise boom control and minimal deflection.



JOYSTICK DESIGN

Ergonomic design features improved thumb controls and system feedback lamps.