

TRAXX RC23

IIIII



TRAXX RC28

Bi-directional cutting reduces the need for turning, dramatically improving productivity, and minimizes surface disturbance.

PERFORMANCE

Featuring a new and powerful 28 HP vanguard gas engine, with low fuel consumption and emissions, combined with a hybrid electric drive delivers a smooth operation.



STABILITY

The chassis design provides a low center of gravity and perfect 50/50 weight distribution for maximum stability and maneuverability in challenging terrain.

55° IN ANY DIRECTION

PRECISE CONTROL

Dual joystick control with a working range of 500 ft, specifically designed for the TRAXX[™]RC28.



ROTARY MULCHING DECK

The TRAXX[™]RC28 features a specially designed 3.6 ft. rotary mulching deck that is capable of producing a quality cut and attractive finish in fine turf applications such as parks and gardens, and tough enough to be used for extensive mowing of heavy grass.



500 ft

458Mhz

Standard

2 x rechargeable batteries

AUTOSTEER TECHNOLOGY

Optional GPS Autosteer technology from Trimble allows it to automatically steer to within 1 in. accuracy along its cutting route for huge advances in output and efficiency.

Trimble



Vanguard 810cc Electronic Fuel Injection (EFI) engine
28hp (21kw)
Gas
2 x 2.6 Gallon, removable tanks

0-4.3 mph ANSI B71.4 safety regulation

Remote Controls

Working range Frequency Battery Proportional joysticks

Engine

Horsepower

Compliance

Fuel tank capacity

Make

Fuel

Speed

Tracks

Universal rubber

Standard ~ max working angle 55°

Mulching Deck Cutting width 3.6 ft Cutting height 1.18 in - 7.08 in Programmable low height setting Standard Bi-directional cutting Standard Updraft, mulching blades Standard Fast-stop rotors Standard (3 second) Dimensions Overall width 59 in Overall length (without attachment) 59 in Overall height 30 in - 36 in

1060 lb

Weight

TRAXX™RC28

Alamo Group (TX) Inc. | 1502 East Walnut Street, Seguin, TX 78155 | 800-882-5762 | www.alamo-industrial.com

This information is intended to be of a general nature only; specifications are subject to change without notice as we continue to improve our products. Warranty: Minimum one year parts and labor. Non-governmental users are subject to a modified policy. Only genuine Alamo Industrial parts may be used for warranty replacement. © 2019 Alamo Group Inc. Registered trademarks identified are property of Alamo Group Inc.