

# Air Flo<sup>®</sup>

**Pro-Class<sup>®</sup> Dump Bodies and Scissor Hoists**

***Get the modern new styled body you want...  
With the quality and durability you need...  
With a Pro-Class<sup>®</sup> Series Body - Only from Air-Flo<sup>®</sup>!***



***Pro-Class<sup>®</sup>***  
***Dump Body***



The single handle tailgate latching system allows for fast and convenient tailgate lowering.



*Pro-Class®* body with drop side option. Hinged sides drop completely vertical. Sides can be easily removed to convert your dump body to a flat bed type body.



Stainless Steel *Pro-Class®* Option. Double sidewall construction and 10 ga. floor made with polished 304 stainless steel will keep this unit shining for years.



The advanced designed scissor hoist provides unmatched loadlifting power with load dumping stability. The entire floor is supported by 3" structural channel cross members on 12" centers.

US and international patents pending

**Features**

- All of the body's horizontal lines and gussets have smooth rounded corners for a classy modern appearance.
- The body sides are constructed of (2) sheets of 10 ga. steel for unsurpassed strength and durability.
- The double wall sides form a fully boxed top rail and include 45° sloped, dirt shedding subrails.
- The 94" wide body is fully welded and made of 10 ga. steel throughout.
- The passenger side mounted singled handle tailgate latching system makes tailgate operations simple, safe and easy.
- The body under structure is built with 3" structural steel channels spaced every 12" and supported by 5" structural channel longitudinals.
- The high lift capacity scissor hoist with factory installed body prop is standard equipment.

**Body Specifications**

Body Length	Side Height	Struck Capacity	Model	Hoist Capacity	Weight
8'	12"	2 Yd.	PCS-8-2	12 Ton	1395
8'	17"	3 Yd.	PCS-8-3	12 Ton	1498
9'	12"	2.3 Yd.	PCS-9-2	11 Ton	1488
9'	17"	3.2 Yd.	PCS-9-3	11 Ton	1604
9'-SS*	17"	3.2 Yd.	PCS-9-3-SS	11 Ton	1554
10'	12"	2.5 Yd.	PCS-10-2	10 Ton	1594
10'	17"	3.5 Yd.	PCS-10-3	10 Ton	1698
10'-SS*	17"	3.5 Yd.	PCS-10-3-SS	10 Ton	1648
11'	12"	3 Yd.	PCS-11-2	9 Ton	1688
11'	17"	4 Yd.	PCS-11-3	9 Ton	1797
12'	12"	3.2 Yd.	PCS-12-2	9 Ton	1788

Hoist capacity rating is based on a 12" body overhang. Tonage capacity will be reduced if overhang is less than 12". \*Stainless Steel Option. Drop side option is not available in stainless steel or 12' bodies.

**Hoist Specifications**

<b>NTEA class</b>	20/40
<b>Cylinder bore &amp; stroke</b>	5" x 20"
<b>Chromed cylinder rod</b>	2"
<b>Max. operating pressure</b>	3200 PSI
<b>Mounting height</b>	9.5"
<b>Weight with subframe</b>	510 lbs.

**CAUTION:** The combined weights of the truck chassis, hoist, body, and cargo must not exceed the gross vehicle rating of the truck.

Air-Flo Manufacturing reserves the right to change design specifications and furnish products so altered without prior notice.



**Air-Flo Manufacturing**

40 South Main Street, Prattsburgh, NY 14873

phone: 607.522.3574

fax: 607.522.4412