

"SDS" SIDE DUMP SPREADER DUMP BODY SERIES

"QUALITY by DESIGN"

- ➤ 24" Cab guard included standard.
- ➤ 7 Gauge sides, tailgate, headsheet.
- ► Dirt shedding lower rub rails.
- ▶ 86" Interior width.
- ▶102" Exterior width.
- Passenger side board pocket integral with tilt floor.





- ► Hoist designed for Spreader/Body use.
- ➤ "Severe service" municipal dump body.
- ► Double acting tailgate.
- ► Corrosion resistant steel construction.
- ► Bolted in 1/4" 400F conveyor floor for maximum servicability.
- ➤ Single axle shown in optional 304SS construction (See left hand picture).





"SDS" SIDE DUMP SPREADER DUMP BODY SERIES



Conveyor uses 667X type pintle chain at 16" wide with 3/8" x 1-1/4" flites on 4-1/2" centers.

The conveyor is a self-cleaning drag chain powered through a reducing gearbox and hydraulic motor.

Optional 304SS Body with 400F Live Floor and wall for additional durability. Body outer walls, headsheet, tailgate utilize 3/16" and 10 gauge 304SS for maximum corrosion resistance. 304SS live floor, wall and conveyor floor available.

Spinner assembly is adjustable to allow you to spread material where you want it. With our adjustable metering door it allows you to limit or increase the amount of material that you move to the spinner. The hydraulically powered spinner disc is 18" round with six (6) vanes. The spinner assembly can be removed for summer use. The chute can be rotated 90° to spread material to the center of the road.



1/4" AR400 live action floor moves material to the conveyor with 36° of lift with the use of two 4" bore by 20" stroke double acting hydraulic lift cylinders. The tilt floor has a polymer wiper to reduce spillage. The body has a fixed right side to increase strength of body. The body can also be used as a conventional dump body. The tailgate has heavy duty flame cut air operated locking ears and 3/8" spreader chains with slot retainers.

Conveyor floor bolted in, not welded for maximum serviceability.

Grease tensioner take-up system with optional roller tensioner available.

OPTIONAL EQUIPMENT

- ► Double acting hoist cylinder.
- ► Coal door (s) in tailgate.
- ▶ "SDS" screen packages.
- ► Roadside polymer chute.
- ▶ 18" polymer spinner.
- ► Folder up ladder
- ► Ladder (2 steps)
- ►3-Way tailgate
- ► Oval light kit
- ▶ 180,000 psi floor
- ➤ 304SS construction with 1/4" AR400 steel floor.





Models Available

SDS bodies are available in 9'-15' lengths. 9'-11' bodies include 30" sides, 39" tailgate. 12'-15' bodies include 38" sides, 50" tailgate. Steel, 304SS, and AR450 Hardox models available.

Everest Equipment Co.

1077 Westmount Ayer's Cliff, QC, Canada J0B 1C0 Tel: (819)-838-4257 Fax: (819)-838-5653

www.everestequipment.com



EVEREST EQUIPMENT CO.

HEAVY- DUTY SNOW & ICE CONTROL

