HPT-B1 & HPT-B2 TUB BODY LINE



DuraClass HPT-B1 shown with available accessories.

> **DuraClass HPT-B2 shown with** distributor-added accessories.



www.duraclass.com

Durability that Means Business



DURABILITY THAT MEANS BUSINESS

BUILT RIGHT

DuraClass **HPT-B1 and B2**, "the TUB" body line, are lightweight champs in a heavyweight world. Semi-elliptical bodies using high tensile steels, crossmemberless understructure, and a body sidewall without extra bracing add up to an exceptional payload-to-weight ratio. The rounded floor and low center of gravity give these bodies the strength and stability for heavy hauling. Loads are discharged cleanly from the curved body shell.




HPT-B1 SPECIFICATIONS												
Inside Length	14'	15'	16'	17'	18'							
Width (inside / outside)	84" / 96"											
Body Capacity, Yards	10-12	12-14	15-17	16-19	17-20							
Material	3/16" Hi-Tensile Steel											
Side Style	Elliptical, closed fender											
Side / Front / Rear Heights (in)	38 / 54 / 44	38 / 54 / 46	44 / 56 / 52	44 / 64 / 52	44 / 68 / 52							
Hoist Model	HPT53-120	HPT53-130	HPT53-140	HPT53-150	HPT53-160							
Understructure	Crossmemberless 10" Beam Longbeams											
Weight (including hoist) (lbs)	4309	4790	5171	5446	5600							





DuraClass bodies come with full depth corner posts and enclosed tailgate hardware, another premium feature you won't find anywhere else in the industry.



BODY OPTIONS

- Aluminum (Cabshields & Tailgates only)
- Sloped Tailgate
- Reverse Asphalt Taper
- Sloping Side Panels
- Hi-Lift Tailgate, Air or Hydraulic
- Dual Action Side Swing Tailgate

D

- Body Side Steps and Handles
- Tarp Rails and Walk Rails
- Variety of Sliding Door Options
- Custom Side and Tailgate Heights
- Air Operated Hoist Controls
- Variety of Cylinder/Doghouse Configurations
- Stainless Steel Bodies available
- Additional Options Available

T-B2

HPT-B2 SPECIFICATION	S													
Inside Length	10' 11'		14'	15'	16'	17'	18'							
Width (inside / outside)	84" / 96"													
Body Capacity, Yards	6-8	6.6-9	10-12	12-14	15-17	16-19	17-20							
Material	3/16" /	AR 400	3/16" Hi-Tensile Steel											
Side Style	Elliptical, open fender													
Side / Front / Rear Heights (in)	28 / 3	8 / 38	38 / 54 / 44	38 / 54 / 46	44 / 56 / 52	44 / 64 / 52	44 / 68 / 52							
Hoist Model	18	21	HPT53-120	HPT53-130	HPT53-140	HPT53-150	HPT53-160							
Understructure	Crossmemberless 10" Beam Longbeams													
Weight (including hoist) (lbs)	ng hoist) (lbs) 2313 2500		4126	4590	4954	5212	5350							

HPT-B2

Greaseable Rear Hinge with Optional Removable Pin.

Elliptical, open fender www.duraclass.com

HPT HOISTS Frameless Head-Mount Design

HPT Benefits:

- Maximized Payload with a lighter weight design
- Increased capacity as a result of high-pressure hydraulics
- Low maintenance design with U-cup cylinder seals that never need adjustment
- **Premium** rear hinge design with wide pedestal style, lubricated hinges and solid pins
- **Better stability** with low center of gravity and strong pin design
- **Increased productivity** with faster cycling, both raising and lowering of body
- Improved longevity with hard chrome plated hoist sleeves

Standard Features

- Two body props
- Fully welded construction



DuraClass 336 Protection...

Rely on our promise to you, 36 months warranty on the 3 most important components of your HPT hydraulic system- the pump, valve and cylinder- if our materials or workmanship fail.

HOIST MODEL	NTEA CLASS	WEIGHT** (LBS)	CAPACITY* (TONS)																
Body Length			10'	11'		12'		13'		14'		15'		16'		17'		18'	
Overhang			12"	6"	12"	6"	12"	6"	12"	12"	18"	12"	18"	12"	18"	12"	18"	12"	18"
HPT53-90	70	670	29.3	23.1	25.5														
HPT53-110	70	725				23.9	26.7												
HPT53-120	80	745						23.3	25.6	23.7	26								
HPT53-130	80	750										23.4	25.3						
HPT63-120	110	985						38.4	42.3	39.1	42.9								
HPT63-130	110	995										38	41.2						
HPT63-140	120	1020												38.1	41.1	36.5	38.8		
HPT63-150	120	1040														38	40.6	36	38.2
HPT63-160	120	1060																37	39.4

*Capacity is based on water-level load and approximately 50° dump angle.

**Weight is less oil and PTO

All bodies shown with some optional equipment. Models and options are subject to change without notice.



1425 Highway 25 North Tishomingo, MS 38873 800.255.4345 Fax: 800.728.4345 www.**duraclass**.com

CONTACT YOUR DISTRIBUTOR

TREE COMPANY

