

The logo consists of the letters 'HC' in a bold, italicized, sans-serif font, outlined in white. It is set against a black, brush-stroke-like background that extends across the top left of the page.

# PUT YOUR FLEET ON THE STREET



## **FISHER® HC**

### Heavy Contractor Snowplows

The 9' and 10' HC Heavy Contractor Snowplows are built for big trucks and designed to move large loads. So no matter what contractors or municipality plow drivers get thrown their way, they can move the snow, then move on to the next parking lot or street.

# FISHER® HC

## Heavy Contractor Snowplows



### STANDARD FEATURES

- Oscillating A-frame for improved scraping and even cutting-edge wear
- Abrasion-resistant curb guards
- Prepunched blade for accessory installation
- 6" top-punch, high-carbon steel cutting edge

### AVAILABLE ACCESSORIES

- Rubber Deflectors
- SnoFoil® Deflector
- Blade Angle Stops
- Shoe Kits
- Carbide Cutting Edge
- 5/8" Cutting Edge

### PLOW BLADE CONSTRUCTION

- 34"-tall, 11-gauge, powder-coated steel blade
- Available in 9' and 10' widths
- Reinforced with eight vertical ribs for carrying heavy snow loads

### HYDRAULICS

- Engineered and built by Fisher Engineering
- Powerful, responsive and built to last
- Critical components are fully enclosed to protect them from the elements

### BUILT STRONG

- Built to withstand heavy-duty commercial and municipal vehicle applications
- Larger hydraulic rams, pins, gussets and hardware
- Proven T-frame design with massive center pin

### TRIP PROTECTION

- Industry-leading trip-edge design protects you and your equipment
- Only the bottom edge trips, so the blade stays upright and snow stays in front
- Compression-type springs never need to be adjusted or wear out

Models	Blade Width	Blade Height	Blade Thickness	Trip Springs	Ribs	Lift Cylinder	Angling Rams	Plowing Width	Approximate Weight	Cutting Edge
HC 9'	9' (2.74 m)	34" (86.36 cm)	11 ga (3.05 mm)	6	8	1 3/4" x 10" (4.45 cm x 25.4 cm)	2" x 12 1/2" (5.08 cm x 31.75 cm)	7' 11" (2.41 m) angled	1100 lb (498.95 kg)	1/2" x 6" (1.27 cm x 15.24 cm)
HC 10'	10' (3.05 m)	34" (86.36 cm)	11 ga (3.05 mm)	6	8	1 3/4" x 10" (4.45 cm x 25.4 cm)	2" x 12 1/2" (5.08 cm x 31.75 cm)	8' 9" (2.67 m) angled	1125 lb (510.29 kg)	1/2" x 6" (1.27 cm x 15.24 cm)



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle weight ratings with a snowplow. This product is manufactured under the following patents US: 6,944,978; 7,400,058; 7,430,821; 7,681,334; 7,737,576; 7,797,859; CAN patents: 2,356,036; 2,632,102; other patents pending. Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, Minute Mount® 2, POLY-CASTER™, SnoFoil®.