

# WARREN

# U-252

## Package Dump Body for Light Duty Trucks

*Warren U-252 package dump bodies are built for top on-the-job performance in day-to-day operation. It is equipped with the Warren model WSC-5519 hydraulic scissor hoist. This body is ideal for trucks having 10,000 GVWR and above. The U-252 is intended for use in hauling most materials used by landscapers, nurserymen, asphalt parking lot and driveway pavers, and municipal and park service maintenance crews. All Warren bodies and hoists are built of ASTM A1011 A-45 High Tensile Steel throughout for long, durable life.*



[www.dumptrucks.com](http://www.dumptrucks.com)  
[www.spreaders.com](http://www.spreaders.com)

Warren, Inc.  
707 North Fir (P.O. Box 1719)  
Collins, MS 39428

Phone: 601-765-8221  
Fax: 601-765-4554  
Toll Free: 800-228-4842

# U-252 Specifications



## Body

Construction:	ASTM A1011 A-45 High Tensile Steel
Understructure:	3" - 4.1#/ft. channel crossmembers 5" - 6.7#/ft channel longitudinals
Floor:	10 ga. steel, 82" inside width; radius edges
Sides:	12 ga. steel, 14" standard height Front and rear gussets 6" high w/ sideboard pockets Full depth rear corner post and skirt Double break top-rail is standard Dirt shedding, sloped rub rails
Tailgate:	12 ga. steel, 6" higher than sides Boxed perimeter bracing Double acting w/ support chains 1 1/4" diameter hinge and latch pins Flame cut steel plate hardware Front lever latch control
Front Bulkhead:	12 ga. steel, 6" higher than sides
Dimensions:	Width: 96" overall, 87" inside Length: 8', 9', 10', & 11'
Capacity:	2/3 cubic yards

## Optional Attachments

- Side & Gate Braces
- Hoist – Gear type pump
- Spreader Apron – 8" (uninstalled)
- 1/4 Cab Shield
- Coal Door (uninstalled)

## Hoists

Type:	Scissor, underbody
Model:	WSC-5519
Pivot Pin:	1 1/4" diameter
Mounting Height:	12" w/ subframe; 8" frameless
Standard Pivot:	12" on 9' & 11' 8" on 8' & 10'
Cylinder:	Type: Single stage, double acting Bore: 5.5" diameter Rod: 2" Chrome Plated Stroke: 18" Displacement: 450 cu. in.
Hydraulic Pump:	Type: Electric 12V DC Capacity: 10.5 GPM @ 1800 RPM
Control Valve:	Double-acting
Controls:	Push button

## Accessories

- Lights/Reflectors: Fed Std. 108, clearance
- Body Prop: Hoist Mounted
- Back Up Alarm: Electric
- Body Up Light: Cab Mounted



Distributed by:



[www.dumptrucks.com](http://www.dumptrucks.com)  
[www.spreaders.com](http://www.spreaders.com)

Warren, Inc.  
707 North Fir (P.O. Box 1719)  
Collins, MS 39428

Phone: 601-765-8221  
Fax: 601-765-4554  
Toll Free: 800-228-4842