



# Growler Mulching Head



Tiger Growler mulching head, the newest addition to Tiger's premium line of boom mower attachments.

The Growler is designed with explosive power to tackle heavy brush and mulch 10" trees into wood chips. It will clear ditches, tree lines and road right-of-ways or other wooded areas with virtually no clean up after the job is complete.

The Tiger Growler head attaches to most existing Tiger booms, making this the perfect addition for all your mowing and clearing needs.



DURABILITY INNOVATION

COMMITMENT



# Tiger Features

## Rugged. Durable. Built to last...

Tiger's reputation for quality and reliability means the Growler's rugged design is built to withstand the harshest conditions and keep on mulching.

The precisely engineered, staggered tooth cutter shaft design provides the operator with a smooth running cutter head.

The precision and engineering integrated into this new head provide strength and performance for tough conditions.

Embrace the power and performance the Growler adds to your operation in clearing miles of small trees and under brush in a single day.



ROAD READY




FRONT VIEW OF MULCHING HEAD



REAR RUBBER FLAP OR REAR CHAIN GUARD



HYDRAULIC DRIVEN HEAD TILT



10" CUT



STOW POSITION



Premium features include a hydraulic tilt cylinder to rotate mulching head, allowing maximum tooth exposure. The Growler Mulching head is also equipped with a piston motor to ensure a quick recovery time and high torque when mulching hardwoods or tough to mulch trees. This piston motor is designed to provide constant torque of the cutter head when taking down a large tree or tough vegetation. This mulching head is retro-fittable to all existing Bengal boom mowers with the purchase of a few additional components and an oil return line. With field-proven performance and strength, the Growler mulching head will allow additional versatility for your roadside mowing tractor package.

## Features

<b>Cut Diameter</b>	10" trees or heavy brush
<b>Cutter Head</b>	36" cutting shaft
<b>Cutter Shaft</b>	Dynamically balanced 12" cutter shaft
<b>Cutter Teeth</b>	30-Rotatable and Replaceable Quad-Cut teeth
<b>Gathering Arms</b>	Designed to bring additional brush and material into cutting drum for 50" total cutting area
<b>Hydraulic Tilt Cylinder</b>	Cylinder gives tilt to cutter head, allowing maximum tooth exposure
<b>Shear Plate</b>	Engineered to cut cut trees or brush into smaller pieces
<b>Cutter Housing</b>	3/8" Domex Steel @ 100,000 Yield Strength
<b>Hydraulic System</b>	Flow is 41.2 GPM with operating pressure at 3000 psi for Bengal and 3500 psi for Saber
<b>Safety Stop</b>	7 Second Shut Down
<b>Weight</b>	930 lbs.

Tiger Corporation  
3301 North Louise Ave.  
Sioux Falls, SD, USA 57107  
800.843.6849  
www.tigermowers.com



## Dealer Info:

An Alamo Group® Company  
Specifications are subject to change. Optional equipment may be shown.

Meets All Applicable ANSI / SAE Test Standards.  
© 2018 Tiger Corporation. All Rights Reserved. Printed in the USA.

