

Landmaster

Professionals who choose Votex, choose powerful machines that deliver maximum performance in all conditions. Whether your business is managing verges, ditches, gardens and parks, or your business is in agriculture or horticulture, Votex machines have been developed to enable you to work safe and responsible. You can also be sure of the best result and an attractive rate per square metre. Votex machines are used in more than 25 countries.

The Votex Landmaster is the flail mower for large areas. It is specially designed for the mowing of green manures, corn stubbles and wastelands. Besides this, the machine can be used for general landscape maintenance.

- Verges and ditches
- Garden, park and public greenery
- Agriculture and horticulture
- Mowers
- Blowers
- Vacuum units and trailers





Sales@Alamo-Industrial.com 1502 E Walnut St, Seguin, TX 78155 | 800-882-5762 |www.alamo-industrial.com

Heavy duty agricultural flail mower

The Landmaster machine comes as standard with 1,3 kg flails for the mowing of the heaviest vegetation. Several options for front or rear mounting turn this machine into a very versatile flail mower. The patented front trailed linkage is optional. This linkage provides you with the benefits of a good view at your work when front mounted, and it follows the exact ground contours when rear mounted. Result: the fastest mower in its category.

Standard options

- Specially designed for cutting green manures and wastelands
- Suitable for heavy landscaping
- Double three-point hitch suitable for both front and rear construction
- Standard equipped with 1,3 kg hammer flails
- Optional front trailed linkage for higher working speeds, better float and lower fuel consumption

Frame	240	275	310
Mouting position	Front or Rear		
Category	Category II and Category III (front trailed cat. II only)		
Safety break system	Not available		
Side shift	Mechanical by linear guidance, optional hydraulic		
Maximal displacement	42 cm (front trailed) / 60 cm (double 3 point)		
Maximum reach (relative to tractor axis)	166 cm	201 cm	192 cm
Mowing head	Ecomow ®		
Flails			
Weight 40 x 12 flail	325 grammes per piece		
Number of 40 x 12 flail	Not available	90	102
Weight hammer flail	1300 grammes per piece		
Number of hammer flails	26	30	36
Power train			
PTO power (min)	50 kW (68 HP)	60 kW (82 HP)	70 kW (95 HP)
PTO speed	540/1000 rpm		
Gearbox	Standard with freewheel		
Dimensions			
Cutting width	237 cm	273 cm	308 cm
Overall width	265 cm	299 cm	331 cm
Weight (from)	840 kg	1025 kg	1115 kg

Specificaties Votex Landmaster



Alamo Industrial* Sales@Alamo-Industrial.com 1502 E Walnut St, Seguin, TX 78155 | 800-882-5762 |www.alamo-industrial.com