

Discover the Maximus



Professionals who choose Votex, choose powerful machines that deliver maximum performance in all conditions. Whether your business is managing verges, ditches, gardens and parks, or your business is in agriculture or horticulture, Votex machines have been developed to enable you to work safe and responsible. You can also be sure of the best result and an attractive rate per square metre. Votex machines are used in more than 25 countries.

- Verges and ditches
- Garden, park and public greenery
- Agriculture and horticulture
- Mowers
- Blowers
- Vacuum units and trailers



Alamo Industrial®

Sales@Alamo-Industrial.com

1502 E Walnut St, Seguin, TX 78155 | 800-882-5762 | www.alamo-industrial.com

Professional side flail mower

The side flail mower for the professional user. The Maximus stands out because of its extremely solid construction and its excellent mowing qualities. Its large capacity, diverse usability and low maintenance make this machine very popular among professional users, including contractors and waterboards.

- Ideal for verges, banks and ditches
- Diverse usability
- Low maintenance
- Power-band transmission and helical gearbox for a silent powertrain
- Mowing angle -60° up to $+90^{\circ}$
- Hydraulic float system to follow ground variations
- Safety break back system if obstacle is struck
- 40 x 12 "J" type flail on twisted shackle for clean finish
- Optional: a rotor axle with 1,3 kg hammerflails
- Hydraulic sideshift of 60 cm



Specifications Maximus					
Frame	120	160	200	240	260
Mounting position	Rear				
Category	Category II and Category III				
Safety break system	Mechanically to the front and rear				
Side shift	Hydraulic by SWING-ON-LINE®				
Maximal displacement	60 cm				
Mowing angle	-60° up to $+90^{\circ}$				
Maximum reach (relative to tractor axis)	293 cm	333 cm	373 cm	413 cm	433 cm
Mowing head	Next Generation				
Flails	325 grammes per piece				
Weight 40 x 12 flail	325 grammes per piece				
Number of 40 x 12 flails	36	48	60	72	78
Weight hammer flail	1300 grammes per piece				
Number of hammer flails	12	16	20	24	28
Power train	540/1000 rpm				
Minimum PTO power	33 kW (45 HP)	44 kW (60 HP)	55 kW (75 HP)	66 kW (90 HP)	72 kW (97 HP)
PTO speed	540/1000 rpm				1000 rpm
Gearbox	Silent box with helical tooth profile				
Dimensions	196 cm				
Cutting width 40 x 12	120 cm	160 cm	201 cm	242 cm	262 cm
Cutting width 1300 g	123 cm	164 cm	205 cm	246 cm	267 cm
Overall width	196 cm				
Weight (from)	1066 kg	1134 kg	1202 kg	1270 kg	1304 kg



Alamo Industrial®

Sales@Alamo-Industrial.com

1502 E Walnut St, Seguin, TX 78155 | 800-882-5762 | www.alamo-industrial.com